

SPIRA PC PUMPS - UNIFORM RUBBER WALL THICKNESS

50 SERIES



1.64 in²

105 SERIES



1.92 in²

140 SERIES



2.04 in²

Available Sizes

Pump Model	Metric	Pump Model Imperial		Stator Top Connection	Stator Bottom Connection	Stator Length		Rotor Connection
	m ³ /day/10 Orpm	Lift Meters	bbbls/day/10 Orpm			Lift Feet	Meters	
50	1000	315	3300	3 1/2-in EUE Box	3 1/2-in EUE Box	4.6	182	1" AP1 Pin
50	1250	315	4100			5.8	228	
50	1500	315	5000			7.0	274	
50	1750	315	5700			9.3	365	
105	750	660	2500	3 1/2-in EUE Box	3 1/2-in EUE Box	7.1	280	1" AP1 Pin
105	900	660	3000			8.5	336	
105	1200	660	4000			11.4	448	
140	600	880	2000	3 1/2-in EUE Box	3 1/2-in EUE Box	7.0	274	1" AP1 Pin
140	900	880	3000			10.4	411	
140	1200	880	4000			13.9	548	

50, 105 & 140 series will drift through 2 7/8" Tubing

50, 105 & 140 series will drift through 3 1/2" Lined Tubing

Other lifts available upon request

50 series is coilable in 3 1/2" tubing