



T2 Artificial Lift Systems - PC Pump Spec Sheet

		PUMP SERIES																				
		"B" 3"	"C" 3 1/2" Barrel			"D" 3 3/4" Barrel						"E" 4 1/4"		"SP" Spira			"F" 5" Barrel			"G" 5.5"	"H" 6.5" Barrel	
Pump Model Metric	m3/day/100rpm	6*	10*	15*	8*	12*	18*	27*	35*	45	60	80	100	50*	105	140	120	160	200	98	165	200
	Lift Meters*	1200	1200	1200	1200	1200	1200	1200	1200	1200	900	900	900	1250	750	600	800	600	500	1200	1200	1200
		1500	1500	1400	1500	1500	1500	1500	1500	1500	1200	1200	1200	1500	900	900	1000	900	700	1600	1600	1600
Pump Model Imperial	bbbs/day/100rpm	38*	65*	95*	50*	80*	110*	170*	220*	285	380	500	630	315*	660	880	755	1000	1250	615	1050	1250
	Lift Feet*	4000	4000	4000	4000	4000	4000	4000	4000	4000	3000	3000	3000	4100	2500	2100	2600	2100	1650	4000	4000	4000
		5000	5000	4600	5000	5000	5000	5000	5000	5000	4000	4000	4000	5000	3000	3000	3300	3000	2500	5250	5250	5250
Stator	Standard Stator Connection EUE	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	5.5" LTC 139.7mm	7" LTC 178mm	7" LTC 178mm
	Optional Stator Connection EUE	3 1/2" 88.9mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	4 1/2" 114mm	5.5" LTC 139.7mm	5.5" LTC 139.7mm
Rotor	API Pin	7/8" 22mm	7/8" 22mm	7/8" 22mm	7/8" 22mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1" 25mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm	1 1/8" 28mm
Tubing	Minimal Tubing to Surface EUE	2 3/8" 84mm	2 3/8" 84mm	2 3/8" 84mm	2 3/8" 84mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	5 1/2" 139.7mm Casing	5 1/2" 139.7mm Casing
	Minimal Tubing Above Stator EUE	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	2 7/8" 73mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	3 1/2" 88.9mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114mm	4 1/2" 114.3mm	7" 178mm Casing	7" 178mm Casing
	Rotor Orbit Diameter	1.9" 48mm	2.3" 59mm	2.4" 61mm	2.3" 59mm	2.5" 64mm	2.6" 66mm	2.6" 66mm	2.6" 66mm	2.6" 66mm	2.8" 71mm	2.8" 71mm	3.3" 71mm	3.3" 74mm	2.7" 69mm	2.9" 74mm	2.9" 74mm	3.8" 97mm	3.8" 97mm	3.8" 97mm	3.8" 97mm	5.0" 127mm

* Pump Series are coilable

Pump Series in Red can be installed into 3 1/2" lined tubing

SP- Spira Pumps are Uniform Wall

Headquarters:

6525-66 Street
Lloydminster, AB Canada
Phone +1 (780) 875-0075
www.t2als.com